

WITPAC

Competence in Heat Transfer.


NOVA-FLEX® 3900 NYLON

NOVA-FLEX® 3900 NYLON

The 3900 Nylon series consists of thin PU-films which have a matt effect. It can be used on all types of plotters and cutting devices.

- Specifically for nylon, acrylic-mixtures and hydrophobic garments
- Available in 12 colours
- Washability: up to 40°C
- Material thickness: 75µ

Due to different quality of garments & heat presses, we recommend to test the materials before any application



Roll sizes:
500mm x 10m, approx 20" x 11yds
other dimensions available on request



Suitable for nylon/ hydrophobic garments and acrylic mixtures



75µ 3 mil	Carrier Material	Polyamide hotmelt
		PU matt face film
		Pressure sensitive adhesive
		Polyester film 100µ



For best results we recommend to store the rolls vertically and away from heat, moisture & direct sunlight



Cold peel



Yes



Wash textile inside out

40°C 104°F	DO NOT DRYCLEAN	TUMBLE DRY	DO NOT USE BLEACH
---------------	-----------------	------------	-------------------

Please wait 24 hours before washing & stretching




145 °C = 293 °F
10 sec.
3-4 bar ≈ 43-58 psi ≈ 3-4 Kg/cm ² medium pressure

WITPAC GmbH
Industrieweg 17
D-48493 Wettringen


Phone: +49 (0) 2557-929 63 66
Mail: info@witpac.de
Website: www.witpac.de

Managing Director: Mr. W. K. Rollfs of Roelofs
VAT-ID.: DE300 924 151
EORI: DE63 279 914 412 67 51
District Court Steinfurt: HRB 10932

sign/service
LEVERANDØR TIL DEN GRAFISKE BRANCHE



01 - WHITE



15 - ORANGE



05 - NAVY BLUE



02 - BLACK



18 - MEDIUM YELLOW



08 - RED



04 - GREEN



30 - SILVER METALLIC



10 - YELLOW



06 - ROYAL BLUE



07 - FOREST GREEN



20 - GOLD METALLIC